

page.tpl.php variables

General Utility Variables

\$base_path	The base URL path of the Drupal installation.
\$directory	The directory the template is located
\$is_front	TRUE if the current page is the front page.
\$logged_in	TRUE if the user is registered and signed in.
\$is_admin	TRUE if the user has permission to access administration pages.

Side Identity

\$front_page	The URL of the front page.
\$logo	The path to the logo image
\$site_name	The name of the site
\$site_slogan	The slogan of the site
\$highlight	Replace of a \$mission

Side Identity

\$title_prefix	An array containing additional output populated by modules
\$title	The page title
\$title_suffix	An array containing additional output populated by modules
\$messages	HTML for status and error messages
\$tabs	Tabs linking to any sub-pages beneath the current page
\$action_links	Actions local to the page
\$feed_icons	A string of all feed icons for the current page.
\$node	The node object

Navigation

\$main_menu	An array containing the Main menu links for the site, if they have been configured.
\$secondary_menu	An array containing the Secondary menu links for the site, if they have been configured.
\$breadcrumb:	The breadcrumb trail for the current page.

html.tpl.php variables

\$css	An array of CSS files for the current page.
\$language	The language the site is being displayed in.
\$language->dir	contains the language direction. It will either be 'ltr' or 'rtl'.
\$language->language	contains its textual representation.
\$head_title	A modified version of the page title, for use in the TITLE tag.
\$head_title_array	An associative array containing title : The title of the current page, if any. name: The name of the site. slogan: The slogan of the site, if any, and if there is no title.
\$head	Markup for the HEAD section (including meta tags, keyword tags, and so on).
\$styles	Style tags necessary to import all CSS files for the page
\$scripts	Script tags necessary to load the JavaScript files and settings for the page.
\$page_top	Initial markup from any modules that have altered the page. This variable should
\$page	The rendered page content.
\$page_bottom	Final closing markup from any modules that have altered the page. This variable should always be output last, after all other dynamic content.
\$classes	String of classes that can be used to style contextually through CSS.

block.tpl.php variables

Available Variables

\$title	Block title
\$content	Block content.
\$block->module	Module that generated the block.
\$block->delta	An ID for the block
\$block->region	The block region embedding the current block
\$classes	String of classes that can be used to style contextually through CSS
\$title_prefix	An array containing additional output populated by modules
\$title_suffix	An array containing additional output populated by modules

Helper Variables

\$classes_array	Array of html class attribute values
\$block_zebra	Outputs 'odd' and 'even' dependent on each block region.
\$zebra	Same output as \$block_zebra but independent of any block region.
\$block_id	Counter dependent on each block region.
\$id	Same output as \$block_id but independent of any block region.
\$is_front	Flags true when presented in the front page
\$logged_in:	lags true when the current user is a logged-in member.
\$is_admin	Flags true when the current user is an administrator.
\$block_html_id	A valid HTML ID and guaranteed unique.

node.tpl.php variables

Available Variables

\$title	The title of the node.
\$content	An array of node items. Use render(\$content) to print them all, or print a subset such as render(\$content['field_example']). Use hide(\$content['field_example']) to temporarily suppress the printing of a given element.
\$user_picture	The node author's picture from user-picture.tpl.php.
\$date	Formatted creation date
\$name	Themed username of node author output from theme_username().
\$terms	the themed list of taxonomy term links output from theme_links().
\$node_url	Direct url of the current node.
\$display_submitted	Whether submission information should be displayed.
\$submitted	Submission information created from \$name and \$date during
\$classes	String of classes that can be used to style contextually through CSS
\$title_prefix	An array containing additional output populated by modules
\$title_suffix	An array containing additional output populated by modules

Other variables

\$node	Full node object
\$type	Node type
\$comment_count	Number of comments attached to the node.
\$uid	User ID of the node author.
\$created	Time the node was published formatted in Unix timestamp.
\$classes_array	Array of html class attribute values.
\$zebra	Outputs either "even" or "odd".
\$id	Position of the node. Increments each time it's output.
\$terms	Outputs taxonomy terms associated to nodes

Node Status

\$view_mode	View mode, e.g. 'full', 'teaser'.
\$teaser	Flag for the teaser state (shortcut for \$view_mode == 'teaser')
\$page:	Flag for the full page state.
\$promote	lag for front page promotion state.
\$sticky	Flags for sticky post setting.
\$status	Flag for published status.
\$comment	State of comment settings for the node.
\$readmore	Flags true if the teaser content of the node cannot hold the main body content.
\$is_front:	Flags true when presented in the front page.
\$logged_in	Flags true when the current user is a logged-in member.
\$is_admin	Flags true when the current user is an administrator.

comment.tpl.php variables

\$author	Comment author
\$content	An array of comment items. Use render(\$content) to print them all, or print a subset such as render(\$content['field_exampl']).
\$created	Formatted date and time for when the comment was created
\$changed	Formatted date and time for when the comment was last changed.
\$new	New comment marker.
\$permalink	Comment permalink.
\$submitted	Submission information created from \$author and \$created
\$picture	Authors picture.
\$signature	Authors signature.
\$status	Comment status
\$title	Linked title.
\$classes	tring of classes that can be used to style contextually through CSS.
\$title_prefix	An array containing additional output populated by modules
\$title_suffix	An array containing additional output populated by modules

Template files		Secondary Menu	<?php print theme('links__system_secondary_menu', array('links' => \$secondary_menu, 'attributes' => array('id' => 'secondary-menu', 'class' => array('links', 'clearfix'),), 'heading' => array('text' => t('Secondary menu'), 'level' => 'h2', 'class' => array('element-invisible'),),)); ?>
[themename].info	meta data, style sheets, JavaScripts, block regions		
html.tpl.php	page wrapper for your theme. Here you have the DOCTYPE declaration, the <head> info, and page closer.		
page.tpl.php	Default theme implementation to display a single Drupal page.		
region.tpl.php	Default theme implementation to display a region.		
block.tpl.php	Default theme implementation to display a block.		
node.tpl.php	Default theme implementation to display a node.		
page--front.tpl.php	Default theme implementation to display a custom frontpage		
node--blog.tpl.php	Default theme implementation to display a node of type blog		
page--node-1.tpl.php	Theme implementation to display page with node ID 1		
block--[region].tpl.php	Theme implementation for block in region name		
html.tpl.php code			
\$header	<head profile=><?php print \$grddl_profile; ?>> <?php print \$head; ?> <title><?php print \$head_title; ?></title> <?php print \$styles; ?> <?php print \$scripts; ?> </head>		
body	<body class=><?php print \$attributes; ?>> <div id=>skip-link</div> #main-menu<?php print t('Jump to Navigation'); ?> </div> <?php print \$page_top; ?> <?php print \$page; ?> <?php print \$page_bottom; ?> </body>		
Logo	<?php if (\$logo): ?> <?php print \$front_page; ?><?php print t('Home'); ?><?php print \$logo; ?><?php print \$logo; ?><?php print t('Home'); ?> <?php endif; ?>		
Site Name	<?php if (\$site_name): ?> <?php if (\$title): ?> <div id=>site-name</div> <?php print \$front_page; ?><?php print t('Home'); ?><?php print \$site_name; ?><?php print \$site_name; ?><?php print \$site_name; ?> </div> <?php else: /* Use h1 when the content title is empty */ ?> <h1 id=>site-name</h1> <?php print \$front_page; ?><?php print t('Home'); ?><?php print \$site_name; ?><?php print \$site_name; ?><?php print \$site_name; ?> <?php endif; ?> <?php endif; ?>		
Site Slogan	<?php if (\$site_slogan): ?> <div id=>site-slogan</div><?php print \$site_slogan; ?></div> <?php endif; ?>		
Header	<?php print render(\$page['header']); ?>		
Highlight	<?php print render(\$page['highlight']); ?>		
Breadcrumb	<?php print \$breadcrumb; ?>		
Title Prefix	<?php print render(\$title_prefix); ?>		
Page Title	<h1 class=>title id=>page-title</h1><?php print \$title; ?></h1>		
Title Suffix	<?php print render(\$title_suffix); ?>		
Messages	<?php print \$messages; ?>		
Tabs	<?php print render(\$tabs); ?>		
Help	<?php print render(\$page['help']); ?>		
Content	<?php print render(\$page['content']); ?>		
Action Links	<ul class=>action-links<?php print render(\$action_links); ?>		
Feed Icon	<?php print \$feed_icons; ?>		
Main Menu	<?php print theme('links__system_main_menu', array('links' => \$main_menu, 'attributes' => array('id' => 'main-menu', 'class' => array('links', 'clearfix'),), 'heading' => array('text' => t('Main menu'), 'level' => 'h2', 'class' => array('element-invisible'),),)); ?>		
Navigation	<?php print render(\$page['navigation']); ?>		
Sidebar Region	<?php print render(\$page['sidebar_first']); ?>		
Footer	<?php print render(\$page['footer']); ?>		
Bottom	<?php print render(\$page['bottom']); ?>		